

DECLARATION OF CONFORMITY

The undersigned, representing the



herewith declares that the

Visually strength graded structural timber

Characteristic	Performance declaration
Species/species group	WPPA: spruce (<i>Picea abies</i>) and pine (<i>Pinus sylvestris</i>)
Growth area	NNE Europe (Northern and North Eastern Europe)
Range of thickness (fire resistance)	25 - 100 mm
Range of width (fire resistance)	50 - 300 mm
Range of length	More than 2,0 m
Surface finish	Sawn or planed
Dry or wet graded	Dry graded
Grade/grading standard	T3, T2, T1 or T0/INSTA 142-SS 230120
Strength, stiffness and density	C30, C24, C18 or C14 (EN 338)
Durability	4 (EN 350-2)
Reaction to fire	D-s2, d0 (EN 14081-1, Table C.1)
Release of dangerous substances	NPD

is in conformity with the provisions of the EC Directive 89/106/CEE (Construction Products Directive - CPD) when intended to be used for structural applications, and that Annex ZA of

EN 14081-1:2005+A1:2011

has been applied.

The CE marking was first applied in 2012.

The notified body SP Technical Research Institute of Sweden (Notified Body 0402) has issued the certificate of factory production control no. **0402-CPD-SC742-12**

Name and address of the company:

Place and date

Lars Carlsson Trävaru AB
Bro
Se-360 23 Älmeboda

Bro, 2012-02-08

Anders Carlsson, VD